

RAILS FOR WELDING CARRIAGES

MR1-RR2M-S(Standard), MR1-RR2M-O(Option)

Rail Rigid aluminum with 2-magnets On-Off switches, 140kgf/magnet weight 4.5kgs



MR1-RR3M-S(Standard), MR1-RR3M-O(Option)

Rail Rigid aluminum with 3-magnets On-Off switches, 140kgf/magnet weight 5.5kgs



MR1-RR3V-S(Standard), MR1-RR3V-O(Option)

Rail Rigid aluminum with 3vacuum cups, a vacuum pump 2.0kgs(6kgs in total)

The pump capacity: 20L/min, vacuum 50~60cm/Hg, 240Vac for vacuum pump



MR1-RF3M-S(Standard), MR1-RF3M-O(Option)

Rail Flexible Special Spring steel with 3-magnets On-Off switches
140kgf/magnet weight 5.5kgs.



Min. Bending Radius : R 1500mm

MR1-RF3V-S(Standard), MR1-RF3V-O

Rail Flexible Special Spring steel with 3-vacuum cups 5.0kgs

A vacuum pump(20L/min, vacuum 50~60cm/Hg, 240Vac, 7.0kgs



Min. Bending Radius : R 1500mm

MR1-RF4M-S(Standard)

Rail Flexible MC Nylon with 4-magnets On-Off swtiches, 2.5kgs



Min. Bending Radius 750mm